

BOLT HORNET

TDH2 DIGITAL HYDRAULIC COACHSCREWING MACHINE



The precision coachscrewing machine that ensures quality and traceability of tightening



Tightening torque precisely controlled

Optimized working time

Geolocated and recorded tightening

HORNET
PORTABLE TECHNOLOGIES

 **GEISMAR**[®]

Your benefits

- Precise and repeatable tightening of coachscrews
- Increased efficiency thanks to automatic adjustment of the three tightening speeds
- Easy preselection of tightening torque and type of fastenings
- Torque and GPS tightening position recording for traceability according to the quality plan
- Ergonomic, adjustable and folding control handles
- Digital screen for easy configuration and control of the tightening torque



Coachscrewing machine specifications

Engine	Honda GX200
Engine power	4.3 kW (5.8 ch)
Socket rotation speed	<ul style="list-style-type: none"> • Low speed: 60/30 tr/min • High speed: 210 tr/min
Mass without trolley	234 lbs (106 kg)
Dimensions in operation (L x l x W)	81.7 x 21.3 x 36.7 in. (2,075 x 540 x 906 mm)
Dimensions in storage (L x l x W)	53.6 x 21.3 x 30.7 in. (1,360 x 540 x 780 mm)
Acoustic level	(Laeq) 84 dB(A) (Lwa) 100 dB(A)
Tightening torque	16 to 55 daN.m
Maximum untightening torque	110 daN.m
Output	≈ 500 tightenings per hour

Standard kit equipment

- Digital hydraulic coachscrewing machine
- Traversing or adherent trolley
(several available dimensions)
- Lighting system
- Key support

Consumables, accessories and maintenance kit

- Sockets/wrenches
(several available dimensions)
- Protective cover
- Packs associated to the TDH2– **ST122A01** et **ST122A02-A6** :

SMARTPACK
KETH2GX2001A

Maintenance kit - 1 year
Engine GX200

LIFE+PACK
KUTDH2-01

Wear & Tear Kit - 01

